

BLACKHAWK

BDR77

The BDR77 features an aggressive, open shoulder tread design which improves self-cleaning to deliver exceptional traction in mud and snow. Its staggered tread block pattern distributes load evenly to resist irregular wear. The BDR77 is engineered with a deep 25/32** tread depth to provide a long tread life. *Exception: 10R22.5, 255/70R22.5.

APPLICATIONS

- Refuse Trucks
- Dump Trucks
- Regional Trucks
- Ready Mix Trucks

TIRE FEATURES

- Open shoulder design delivers superior traction.
- Staggered tread blocks resist irregular wear.
- Deep tread depth for excellent tread life.

Le BDR77 se caractérise par son design d'allure agressive et son épaulement ouvert, qui améliore l'autonettoyage pour une traction exceptionnelle dans la boue et la neige. Le motif décalé des blocs de la semelle répartit la charge uniformément pour résister à l'usure irrégulière. Le BDR77 est muni d'une semelle de 25/32e* de pouce, ce qui favorise une longue durée de vie. *Exception: 10R22.5, 255/70R22.5.

UTILISATIONS

- Service régional
- Camions à benne
- Transport des ordures
- Bétonnières

CARACTÉRISTIQUES

- L'épaulement ouvert favorise une traction supérieure.
- Les blocs massifs décalés résistent à l'usure irrégulière.
- La profondeur de la semelle favorise une durée de vie prolongée.



Size	Ply	T.D.	Load Index		S.R.	O.D.	S.W.	R.W.	Load Carrying Capacity		A.P.
		32nds	Single	Dual					Single, lbs.	Dual, lbs.	
10R22.5	14	23	141	139	M	40.6	10.0	7.50	5,675	5,355	115
11R22.5	14	25	144	142	L	41.5	11.0	8.25	6,175	5,840	105
11R22.5	16	25	146	143	L	41.5	11.0	8.25	6,610	6,005	120
255/70R22.5	16	24	140	137	L	36.9	10.0	7.50	5,510	5,070	120
11R24.5	14	25	146	143	L	43.5	11.0	8.25	6,610	6,005	105
11R24.5	16	25	149	146	L	43.5	11.0	8.25	7,160	6,610	120